NP AI PRIMECOAT

Jan'26

NP AI Primecoat is a non-ionic water-based densifier & function as anti-stick coating between original automotive paint & AI Topcoat. It can form a thin & dense coating layer on the substrate by spraying or wiping, improving the AI Topcoat film smoothness and peel-ability properties from original automotive paint.

Product Features:

- Anti-stick coating between AI Topcoat & original automotive paint
- Improve on AI Topcoat film smoothness
- Improve on peel-ability properties of AI Topcoat

Paint Type	Product Type	Recommended Substrate	Pack Size
Water based	Automotive	Automotive paint surface	300ml

Mixing Ratio

Ready to use

Technical Data

Physical form : Light yellowish liquid
pH :7.0 – 10.0
Shelf life : 9 months from date of manufacturing (original sealed container)

Application Method

Spraying Recommendation :

Spray-gun type	Nozzle size	Application pressure
LVLP Gravity	1.0 mm	1.0-1.2 bar at the spray gun air inlet
HVLP Gravity	1.0 mm	1.0-1.2 bar at the air cap

Spraying Viscosity @ 30^{o}C : Ready to use

Safety Precautions

- Keep container tightly closed and keep out of reach from children or away from food and drink.
- Ensure good ventilation during application and drying.
- When applying product, it is advisable to wear eye protection.
- In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
- Remove splashes from skin by using soap or water.
- Product must always be stored in a cool place.
- When transporting product, care must be taken. Always keep container in a secure upright position.
- Dispose of any product waste in accordance with the appropriate Environment Quality Regulations.