NIPPON PAINT MALAYSIA SDN. BHD.
TECHNICAL DATA SHEET

NP 512 2K THINNER

Description & Application

- NP 512 2K Thinner is a premium 2K thinner which is highly recommend to be used for diluting 2K primer, basecoat and clearcoat.
- This high performance thinner will improve film smoothness of 2K clear thus providing excellent finish on the final appearance.
- Supports the applied 2K solid topcoat or clearcoat blending into the existing finish on the surface.
- User friendly with good flow properties.
- Recommended usage as per technical datasheet or application guide for the specific product to be applied.

Composition

Aromatic Hydrocarbon	: 50 – 60 %
Ester	: 40 – 50 %

Typical Properties

Specific Gravity@25°C	: 0.85 – 0.95 Kg/L
Flash Point	: 36°C
Appearance (Color)	: Water Clear Solution

Precaution

Fire Hazard	: Flammable Liquid
Toxicity	: Avoid excessive skin contact & inhalation of vapours

Other Information

Shelf life	: 36 months from date of manufacturing (original sealed container)

The properties mentioned above are tested on good quality pre-treated substrate and are subject to change according to the shade/colour of the material without any prior notice. The technical information and the suggestions for use are based on laboratory test results and practical experience. We urge that users of our materials conduct confirmatory tests to determine final suitability for their specific end uses.

REV: Updated May/2022